

PHILIPPINE SPORTS COMMISSION

REQUEST FOR QUOTATION

The Philippine Sports Commission, through its Bids & Awards Committee, invites interested **PHILGEPS-accredited** suppliers to **submit SEALED signed quotation/s** for:

Particular	Quantity			ABC (PHP)	Place of Delivery
	Description	Qty	Unit		
Supply and Delivery of Digital Multimeter and Clamp Meter for Various Repair works of Defective Air-Conditioning Units and other Equipment in all Venues of RMSC	<p>1 Digital Multimeter (Branded)</p> <ul style="list-style-type: none"> >Operation Method: Δ-Σ method >AC Measuring Method: True RMS value Method >LCD: 4000 Counts >Sampling Rate: Approx. 3 Times/Sec. >Range Section: Auto and Manual (Some with Manual or Auto only) >Overall Range Indication: "OL" shown in numerical part (1000V DC/AC, 10A excluded. 600V DC/AC Excluded) >Polarity Indication: "-" indicate only hen negative input >Low Battery indication: \pm Mark light or flickers at approx. 2.4V or below >Environmental Condition: Altitude 2,000m or Below, Pollution degree II >Operating Temperature/Humidity: 5° C to 40° C and Maximum relative humidity at 40° C (No Condensation) >Storage temperature /humidity: - 10 °C to 40° C, 80% RH Max., 40° to 50° C, 70% RH Max no condensation >Power Supply: Sum 3(R6), 2 Pieces >Battery Life at DCV: Approx. 150h (disable auto power off) >Auto Power off: About 30 min. after the last operation >Fuse: 0.5A/1000V, breaker capacity 30kA 16A/1000V, breaking capacity 30kA >Safety Standards: IEC61010-1 CAT. III 1000V IEC61010-031 >EMC Directive: IEC61326 >Dimension: 166(L) x 82 (W) x 44 (D)mm (Projection not Included) 	1	Set	39,030.00	Property and Supplies Office, Rizal Memorial Sports Complex, P. Ocampo Sr. St. (Formerly Vito Cruz), Malate, Manila.

>Weight: Approx. 360 (Batteries included)
 >Power Consumption: 15mW at DCV (Typical)
 >Standard Accessories included: Test lead (TL-25)
 Battery (Built in)
 Sheath slape
 thermocouple K type
 (k-250CD)
 Inspection certificate/
 Instruction manual
 >Optional accessories: Alligator clip: CL-11,CL-15,TL-81C
 Clamp probe: CI-22AD, CL-33DC,CL-20D
 Carrying case: C-77
 Temperature probe:K-8-800,K-8-650,K-8-300,K-8-500,
 K-8-250
 K type Adaptor,K-AD

2 Clamp Meter (Branded)

>ACA: 200/2000A,±(2.0%+5),0.1A
 >DCA: 200/2000A,±(2.0%+5),0.1A
 >ACV: 6/60/600/1000V,±(1.2%+5),0.001A
 >DCV: 6/60/600/1000V,±(0.5%+5),0.001A
 >Resistance: 600/6k/60k/600k/6M/40M Ω
 ±(0.5%+5),0.1 Ω
 >Frequency: 10-1999Hz,±(0.1%+4),0.01Hz
 >Capacitance: 60n/600n/6 u/60 u/2000 uF
 >Continuity: Buzzer sounds at between 10Ω and 200Ω
 Open Voltage: approx. 0.5V
 >Diode Test: Open voltage: approx. 1.8V
 >Bandwidth: 50-400Hz
 >Display: 6000
 >Clamp diameter/Conductor Size: 55 mm/20x66mm
 >Battery: R6 x 2
 >Size/Mass: H264xW97xD43mm/approx.640g
 >Standard accessories included: Test lead(TL-29),
 carrying case,Instruction manual

****Nothing Follows****

The following documents must be submitted from April 4-10, 2018, 5:00 p.m. to the Office of Procurement located at 2nd floor, Administration Building, Rizal Memorial Sports Complex, Pablo Ocampo Sr. St. (Formerly Vito Cruz), Malate, Manila.

1. PHILGEPS Registration or PHILGEPS Certificate
2. ITR Form Year 2016 or Tax Clearance
3. Omnibus Sworn Statement (Notarized)
4. Mayor's Permit

For additional information, please contact the Procurement Office at Telefax: 524-3512 or 525-0808 Loc. 175/143.

The Commission reserves the right to not accept any and all quotations or not award the contract on the following grounds:

- There is prima facie evidence of collusion;
- The BAC failed to follow prescribed procurement procedures; and or
- There are justifiable grounds where the contract will not redound to the benefit of the government without incurring any liability to the affected bidder/s.

ATTY. GUILLERMO B. IROY, JR.
 BAC Chairman

APR 10 2018

Date Posted on PSC website: April 4, 2018